

EMCOR CONVENTIONAL AIR DRY APPLICATION INSTRUCTIONS

EMCOR CONVENTIONAL AIR DRY is of the finest quality. Mix contents thoroughly before using. Contents need to be applied to a clean prepared surface. For best results, this acrylic coating should be applied without reduction and by spray application. Reduction information is available upon request. EMCOR conventional air dry is designed to be applied to steel substrates. Non-ferrous application information is available upon request. Drying time on properly applied coatings of 1.2 to 1.5 millimeters is 15 minutes dust free, 1 hour dry to touch, and 4 hours dry to be handled. Straining material before use is suggested. The temperature of the substrate and the temperature of the air, must exceed 65 degrees F for proper application.

WARNING! HARMFUL IF SWALLOWED. MAY CAUSE LIGHT/MODERATE SKIN IRRITATION AND SEVERE EYE IRRITATION. MAY BE ABSORBED THROUGH THE SKIN. PROLONGED OR REPEATED CONTACT MAY CAUSE AN ALLERGIC SKIN REACTION. VAPOR AND/OR SPRAY MIST MAY BE HARMFUL IF INHALED. SANDING AND GRINDING DUSTS MAY BE HARMFUL IF INHALED. VAPOR IRRITATES EYES, NOSE AND THROAT. FLAMMABLE. Keep away from heat, sparks, flames, and other sources of ignition. Do not smoke. Extinguish all flames and pilot lights, Turn off stoves, heaters, electrical motors, and other sources of ignition during use and until all vapors/odors are gone.

Contains: TITANIUM DIOXIDE, AMORPHOUS SILICA, NAPHTHA, ESTERS

Prevent contact with skin, eyes or clothing and breathing of vapors and spray mist. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Eye watering, headaches, nausea, dizziness and loss of coordination are indications that solvent levels are too high. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Wear chemical-type splash goggles or full-face shield and protective clothing, including impermeable apron and gloves. USE WITH ADEQUATE VENTILATION. Overexposure to vapors may be prevented by ensuring proper ventilation controls, vapor exhaust or fresh air entry. An NIOSH-approved air purifying respirator with the appropriate chemical cartridges or a positive-pressure, air-supplied respirator may also reduce exposure. Follow the respirator manufacturer's directions for respirator use. Contact with flame or hot surfaces may produce toxic decomposition products (see MSDS). This product is photochemically reactive pursuant to SCAQMD rule 102.

FIRST AID: If swallowed, do not induce vomiting. Gently wipe our inside of mouth to remove any residual material. In case of skin contact, flush immediately with plenty of water for at least 15 minutes followed by washing with soap and water. In case of eye contact, remove contact lenses and flush eyes immediately with a gentle stream of luke warm water for at least 15 minutes. If affected by inhalation of vapor or spray mist, remove to fresh air. Apply artificial respiration and other support measures as required.

If ingestion, any type of overexposure, or symptoms of overexposure occur during or following the use of this product, contact a

POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN IMMEDIATELY; have label information available. Close container after each use. KEEP OUT OF THE REACH OF CHILDREN. Emergency Medical of Spill Control Information in U.S. (800) 424-9300. See MATERIAL SAFETY DATA SHEET.

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

DISPOSE OF CONTAINER PROPERLY
FOR INDUSTRIAL AND PROFESSIONAL USE ONLY
GALLON U.S. MEASURE
MADE AND PRINTED IN USA